## NSN 5920-00-852-7299

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-852-7299 **Body Style:** Panel mounted type **Overall Length:** 3.750 inches **Bushing Diameter:** 0.866 inches **Overall Height:** 1.812 inches **Overall Width:** 1.188 inches **Mounting Hole Diameter:** 0.156 inches **Mounting Hole Quantity: Environmental Protection:** Fungus proof **Mounting Hole Style:** 2 bushing mounting w/2 holes **Lens Color:** Clear **Contact Material: Brass Contact Surface Treatment:** Silver plated **Interruption Indicator Method:** Neon lamp **Fuse Accommodation Quantity: Accommodated Fuse Length:** 1.250 inches **Accommodated Ferrule Diameter:** 0.250 inches **Resistor Rating:** 120.0 kilohms **Length From Front Protrusion To Mounting Surface:** 0.813 inches Center To Center Distance Between Outside Mounting Holes Along Length: 0.926 inches Center To Center Distance Between Outside Mounting Holes Along Width: 0.926 inches

**Bushing Hole Diameter:** 

0.866 inches

## NSN 5920-00-852-7299

Extractor Post Fuseholder - Page 2 of 2



Center To Center Distance Between Bushing Holes:	
0.800 inches	
Center To Center Distance Between Keyway And Bushing Hole:	
0.463 inches	
Screw Thread Diameter:	
0.164 inches	
Screw Thready Qty Per Inch (tpi):	
32.0	
Current Carrying Rating In Amps:	
30.0	
Fuse Terminal Type Accommodated:	
Ferrule	
Voltage In Volts:	
125.0	
Terminal Type And Quantity:	
4 threaded stud	
Shelf Life:	
N/a	
Unit Of Measure:	
Demilitarization:	
No	
Fiig:	
A014a0	