NSN 5920-00-853-0177

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-00-853-0177

| View Online at https://aeroba | Isegroup.com/nsn/5920-00-853-0177 |
|--------------------------------|--|
| Body Style: | |
| Tube type | |
| Terminal Material: | |
| Brass | |
| Terminal Surface Treatmen | ıt: |
| Silver plated | |
| Overall Length: | |
| Between 1.969 inches and 2 | .031 inches |
| Overall Diameter: | |
| Between 0.556 inches and 0. | .568 inches |
| Case Material: | |
| Plastic, melamine, glass fille | ed |
| Continuous Current Rating | In Amps: |
| 1.000 | |
| Maximum Voltage Rating Ir | า Volts: |
| 500.0 ac and 500.0 dc | |
| Circuit Over-current Interru | iption Type: |
| Normal instantaneous | |
| Interruption Indicator Meth | od: |
| Opaque body | |
| Features Provided: | |
| Nonrenewable fusible element | nt |
| Short-circuit/interrupt Curr | ent Rating In Amps: |
| 5000.0 and 68000.0 | |
| Precious Material And Loca | ation: |
| Terminal surfaces silver | |
| Precious Material: | |
| Silver | |
| Test Data Document: | |
| 81349-mil-f-15160 specificati | ion (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercia | l catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performar | nce requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: | |
| 81349-mil-f-15160/61 govern | ment specification |
| Shelf Life: | |
| N/a | |
| Unit Of Measure: | |
| | |
| Demilitarization: | |
| No | |

Fiig:

A01700