

View Online at <https://aerobasegroup.com/nsn/5920-00-855-4259>

Body Style:

Tube type

Terminal Material:

Brass or copper or copper alloy

Terminal Surface Treatment:

Silver plated

Overall Length:

Between 1.469 inches and 1.531 inches

Overall Diameter:

Between 0.402 inches and 0.410 inches

Case Material:

Fiber

Continuous Current Rating In Amps:

3.200

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Circuit Over-current Interruption Type:

Time delay

Interruption Indicator Method:

Opaque body

End Application:

Nkilauea class t-ae 26; guided missile launching systems, mk 26 (gmls); oliver perry class ffg; virginia class cgn (41) kidd class ddg; degaussing equipment; nimitz class cvn; forrestal class cv; teletype, model 28

Features Provided:

Nonrenewable fusible element

Circuit Over-current Interruption Delay Time In Seconds:

12.0 200 pct of current rating

Criticality Code Justification:

Feat

Short-circuit/interrupt Current Rating In Amps:

35.0

Special Features:

Weapon system essential

Precious Material And Location:

Terminal surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15160/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A01700