

View Online at <https://aerobasegroup.com/nsn/5920-00-872-8205>

Body Style:

Rear panel mounted type

Overall Length:

Between 3.750 inches and 4.000 inches

Overall Height:

1.188 inches

Overall Width:

1.062 inches

Keyway Width:

0.210 inches

Mounting Hole Diameter:

Between 0.145 inches and 0.150 inches

Mounting Hole Quantity:

2

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting w/2 holes and keyway

Contact Material:

Copper, qq-c-502

Contact Surface Treatment:

Silver plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

124.0 kilohms

Indicating Lamp Voltage Range In Volts:

+80.0/+135.0

Length From Front Protrusion To Mounting Surface:

0.812 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.705 inches and 0.725 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.890 inches and 0.908 inches

Bushing Hole Diameter:

Between 0.850 inches and 0.860 inches

Center To Center Distance Between Keyway And Bushing Hole:

Between 0.445 inches and 0.454 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Terminal Type And Quantity:

2 threaded stud

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0