

View Online at <https://aerobasegroup.com/nsn/5920-00-878-0790>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type sdg

**Body Style:**

Panel mounted type

**Overall Length:**

Between 3.750 inches and 4.000 inches

**Overall Height:**

Between 1.812 inches and 1.817 inches

**Overall Width:**

Between 1.180 inches and 1.185 inches

**Mounting Hole Diameter:**

Between 0.151 inches and 0.161 inches

**Mounting Hole Quantity:**

2

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

2 bushing mounting w/2 holes

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Interruption Indicator Method:**

Incandescent lamp

**Fuse Accommodation Quantity:**

2

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

1.2 kilohms

**Indicating Lamp Voltage Range In Volts:**

+46.0/+60.0

**Length From Front Protrusion To Mounting Surface:**

Between 0.798 inches and 0.828 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

Between 0.933 inches and 0.943 inches

**Bushing Hole Diameter:**

Between 0.869 inches and 0.879 inches

**Center To Center Distance Between Bushing Holes:**

Between 0.795 inches and 0.805 inches

**Center To Center Distance Between Keyway And Bushing Hole:**

Between 0.464 inches and 0.474 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

60.0

**Test Data Document:**

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

4 threaded stud

**Specification Data:**

81349-mil-f-19207/18 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0