

View Online at <https://aerobasegroup.com/nsn/5920-00-878-8907>

**Overall Depth:**

1.728 inches

**Center To Center Distance Between Mounting Facilities Parallel To Width:**

4.375 inches

**Overall Height:**

3.375 inches

**Overall Width:**

4.812 inches

**Unthreaded Mounting Hole Diameter:**

Between 0.145 inches and 0.156 inches

**Standard Mounting Pattern Designator:**

6 point-rectangular

**System For Which Designed:**

Three wire three phase and three wire dc

**Fuse Current Rating In Amps:**

3.0 and 6.0

**Mounting Method:**

Flange w/hole

**Locking Device Type:**

Latch

**First Center To Center Distance Between Mounting Facilities Parallel To The Height:**

0.812 inches

**Second Center To Center Distance Between Mounting Facilities Parallel To The Height:**

0.812 inches

**Main Line Maximum Current Rating In Amps:**

30.0

**Main Line Maximum Ac Voltage Rating In Volts:**

2000.0

**Main Line Maximum Dc Voltage Rating In Volts:**

850.0

**Ground Connection Type For Which Designed:**

Insulated

**Fuse Type And Quantity Accommodated:**

6 cartridge ferrule

**Features Provided:**

Cover

**Entrance Type And Quantity:**

1 rectangular/square

**Material:**

Aluminum alloy

**Surface Treatment:**

Anodize

**Style Designator:**

Rectangular, surface mounting

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A17600