

View Online at <https://aerobasegroup.com/nsn/5920-00-887-6514>

Body Material:

Plastic, diallyl phthalate, mil-m-19833, type gdi-30f

Body Style:

Shielded-bushing mounted type

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

2.660 inches

Mounting Hole Quantity:

1

Body Length:

2.500 inches

Overall Diameter:

Between 0.870 inches and 0.880 inches

Environmental Protection:

Watertight

Mounting Hole Style:

Bushing mounting

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

Between 0.920 inches and 0.960 inches

Bushing Thread Length:

0.500 inches

Cap Diameter:

Between 0.870 inches and 0.880 inches

Bushing Hole Diameter:

Between 0.500 inches and 0.510 inches

Flatted Side Bushing Hole Length:

Between 0.468 inches and 0.478 inches

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Precious Material And Location:

Terminals gold and terminal surfaces silver

Precious Material:

Gold and silver

Test Data Document:

81349-mil-f-19207/36 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0