

View Online at <https://aerobasegroup.com/nsn/5920-00-892-9395>

**Body Material:**

Plastic, diallyl phthalate, mil-m-19833, type gdi-30f

**Body Style:**

Bushing mounted type

**Terminal Surface Treatment:**

Solder dip and tin plated

**Overall Length:**

2.340 inches

**Bushing Diameter:**

0.500 inches

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.000 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Length From Front Protrusion To Mounting Surface:**

Between 0.630 inches and 0.670 inches

**Bushing Thread Length:**

Between 0.450 inches and 0.490 inches

**Cap Diameter:**

Between 0.680 inches and 0.690 inches

**Bushing Hole Diameter:**

Between 0.500 inches and 0.510 inches

**Flatted Side Bushing Hole Length:**

Between 0.468 inches and 0.478 inches

**Current Carrying Rating In Amps:**

5.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Test Data Document:**

81349-mil-f-19207/20 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0