NSN 5920-00-894-1045

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-894-1045

The state of the s
Body Style:
Tube type
Terminal Material:
Brass or copper or copper alloy
Terminal Surface Treatment:
Silver plated
Overall Length:
1.500 inches
Overall Diameter:
0.406 inches
Case Material:
Fiber
Continuous Current Rating In Amps:
2.000
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
12.0 200 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
35.0
Precious Material And Location:
Terminal surfaces silver
Precious Material:
Silver
Test Data Document:
Mil-prf-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349 - mil-prf-15160/9 government specification
Shelf Life:
N/a
Unit Of Measure:

Demilitarization:
No

Fiig: A01700

NSN 5920-00-894-1045

Cartridge Fuse - Page 2 of 2



Mil-std (military Standard):

Mil-prf-15160 spec.