## NSN 5920-00-900-0209

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-900-0209

**Body Material:** 

Plastic, diallyl phthalate, mil-m-14, type sdg

**Body Style:** 

Panel mounted type

**Terminal Material:** 

**Brass** 

**Overall Length:** 

Between 2.360 inches and 2.400 inches

**Overall Height:** 

Between 2.170 inches and 2.210 inches

**Overall Width:** 

Between 1.040 inches and 1.080 inches

**Mounting Hole Diameter:** 

Between 0.147 inches and 0.157 inches

**Mounting Hole Quantity:** 

4

**Environmental Protection:** 

Watertight and body sealed

**Mounting Hole Style:** 

3 bushing mounting w/4 holes

**Contact Material:** 

Copper

**Contact Surface Treatment:** 

Silver plated, qq-s-365

**Fuse Accommodation Quantity:** 

3

**Accommodated Fuse Length:** 

1.250 inches

**Accommodated Ferrule Diameter:** 

0.250 inches

**Length From Front Protrusion To Mounting Surface:** 

Between 0.540 inches and 0.580 inches

Cap Diameter:

Between 0.600 inches and 0.640 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.745 inches and 0.755 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.495 inches and 0.505 inches

**Bushing Hole Diameter:** 

Between 0.583 inches and 0.598 inches

**Center To Center Distance Between Bushing Holes:** 

Between 0.745 inches and 0.757 inches

## **NSN 5920-00-900-0209**Extractor Post Fuseholder - Page 2 of 2



Err Default:
Err default and err default
Screw Thread Diameter:
0.138 inches
Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
250.0
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Test Data Document:
81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
3 threaded stud and 3 screw
Specification Data:
81349-mil-f-19207/30 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A014a0