

View Online at <https://aerobasegroup.com/nsn/5920-00-900-0209>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Panel mounted type

Terminal Material:

Brass

Overall Length:

Between 2.360 inches and 2.400 inches

Overall Height:

Between 2.170 inches and 2.210 inches

Overall Width:

Between 1.040 inches and 1.080 inches

Mounting Hole Diameter:

Between 0.147 inches and 0.157 inches

Mounting Hole Quantity:

4

Environmental Protection:

Watertight and body sealed

Mounting Hole Style:

3 bushing mounting w/4 holes

Contact Material:

Copper

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

3

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

Between 0.540 inches and 0.580 inches

Cap Diameter:

Between 0.600 inches and 0.640 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.745 inches and 0.755 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.495 inches and 0.505 inches

Bushing Hole Diameter:

Between 0.583 inches and 0.598 inches

Center To Center Distance Between Bushing Holes:

Between 0.745 inches and 0.757 inches

Err Default:

Err default and err default

Screw Thread Diameter:

0.138 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

3 threaded stud and 3 screw

Specification Data:

81349-mil-f-19207/30 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0