NSN 5920-00-900-8839Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-900-8839
Body Style:
Axial terminal type
Terminal Material:
Brass
Terminal Surface Treatment:
Nickel
Overall Length:
3.000 inches
Center To Center Distance Between Mounting Facilities Parallel To Length:
Between 2.469 inches and 2.531 inches
Mounting Slot Width:
Between 0.235 inches and 0.297 inches
Body Length:
Between 1.844 inches and 1.906 inches
Overall Diameter:
Between 0.531 inches and 0.593 inches
Case Material:
Fiber
Continuous Current Rating In Amps:
30.000
Terminal Width:
Between 0.469 inches and 0.531 inches
Maximum Voltage Rating In Volts:
125.0 ac and 125.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
30.0 300 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
10000.0
Test Data Document:
81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-f-15160/37 government specification
Shelf Life:
N/a

Unit Of Measure:

NSN 5920-00-900-8839Cartridge Fuse - Page 2 of 2



Demilitarization:

No

Fiig:

A01700