

View Online at <https://aerobasegroup.com/nsn/5920-00-902-2377>

**Body Material:**

Plastic, diallyl phthalate, mil-m-14, type sdg

**Body Style:**

Rear panel mounted type

**Terminal Material:**

Brass

**Overall Length:**

Between 3.750 inches and 4.000 inches

**Overall Height:**

Between 1.200 inches and 1.205 inches

**Overall Width:**

Between 1.068 inches and 1.072 inches

**Keyway Width:**

0.200 inches

**Mounting Hole Diameter:**

Between 0.151 inches and 0.161 inches

**Mounting Hole Quantity:**

2

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting w/2 holes and keyway

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

120.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+90.0/+250.0

**Length From Front Protrusion To Mounting Surface:**

Between 0.798 inches and 0.828 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

Between 0.745 inches and 0.755 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

Between 0.870 inches and 0.880 inches

**Bushing Hole Diameter:**

Between 0.870 inches and 0.880 inches

**Center To Center Distance Between Keyway And Bushing Hole:**

Between 0.432 inches and 0.442 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Test Data Document:**

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded stud

**Specification Data:**

81349-mil-f-19207/2 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0