NSN 5920-00-904-1370

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-904-1370 **Body Material:** Plastic, diallyl phthalate, mil-m-14, type sdg **Body Style:** Bushing mounted type **Terminal Surface Treatment:** Tin plated **Overall Length:** 3.281 inches **Bushing Diameter:** 0.625 inches **Overall Diameter:** 0.812 inches **Environmental Protection:** Dripproof **Mounting Hole Style: Bushing mounting Contact Material: Brass Contact Surface Treatment:** Any acceptable **Interruption Indicator Method:** Neon lamp **Fuse Accommodation Quantity: Accommodated Fuse Length:** 1.250 inches **Accommodated Ferrule Diameter:** 0.250 inches **Resistor Rating:** 220.0 kilohms **Indicating Lamp Voltage Range In Volts:** +90.0/+250.0 **Length From Front Protrusion To Mounting Surface:** 1.188 inches **Bushing Thread Length:** 0.438 inches **Current Carrying Rating In Amps:** 20.0 **Fuse Terminal Type Accommodated:**

Ferrule

Voltage In Volts:

250.0

NSN 5920-00-904-1370

Extractor Post Fuseholder - Page 2 of 2



Test Data Document:

71400-hkrejqrwaazz specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

| Termina | Type A | And C | Quantity: |
|---------|--------|-------|-----------|
|---------|--------|-------|-----------|

| 2 | tab. | solder | lua |
|---|------|--------|-----|
| _ | iuo, | Joidei | IUU |

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0