

View Online at <https://aerobasegroup.com/nsn/5920-00-914-7467>

**Body Material:**

Plastic, diallyl phthalate, mil-m-19833, type gdi-30f

**Body Style:**

Panel mounted type

**Terminal Material:**

Brass or copper

**Terminal Surface Treatment:**

Solder dip and tin plated

**Overall Length:**

Between 1.132 inches and 1.179 inches

**Bushing Diameter:**

0.625 inches

**Mounting Hole Quantity:**

1

**Overall Diameter:**

0.687 inches

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting

**Lens Color:**

Clear

**Contact Material:**

Beryllium copper

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

0.518 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

330.0 ohms

**Indicating Lamp Voltage Range In Volts:**

+23.0/+33.0

**Length From Front Protrusion To Mounting Surface:**

Between 0.530 inches and 0.570 inches

**Test Data Document:**

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-f-19207/28 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0