

View Online at <https://aerobasegroup.com/nsn/5920-00-921-4898>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Rear panel mounted type

Terminal Material:

Brass

Overall Length:

Between 3.750 inches and 4.000 inches

Overall Height:

Between 1.200 inches and 1.205 inches

Overall Width:

Between 1.068 inches and 1.072 inches

Keyway Width:

0.105 inches

Mounting Hole Diameter:

Between 0.151 inches and 0.161 inches

Mounting Hole Quantity:

2

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting w/2 holes and keyway

Lens Color:

Amber

Contact Material:

Beryllium copper

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Incandescent lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Indicating Lamp Voltage Range In Volts:

+12.0/+22.0

Length From Front Protrusion To Mounting Surface:

Between 0.798 inches and 0.828 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 0.745 inches and 0.755 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 0.870 inches and 0.880 inches

Bushing Hole Diameter:

Between 0.870 inches and 0.880 inches

Center To Center Distance Between Keyway And Bushing Hole:

Between 0.432 inches and 0.442 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

22.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Specification Data:

81349-mil-f-19207/19 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0