

View Online at <https://aerobasegroup.com/nsn/5920-00-926-7464>

Body Material:

Plastic, mil-p-14, type mai-60

Body Style:

Bushing mounted type

Overall Length:

3.025 inches

Bushing Diameter:

Any acceptable

Mounting Hole Quantity:

1

Overall Diameter:

1.380 inches

Panel Thickness:

0.125 inches

Environmental Protection:

Watertight and body sealed

Mounting Hole Style:

Bushing mounting

Lens Color:

Amber

Contact Material:

Beryllium copper

Contact Surface Treatment:

Any acceptable

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Resistor Rating:

330.0 kilohms

Indicating Lamp Voltage Range In Volts:

+23.0/+33.0

Length From Front Protrusion To Mounting Surface:

1.120 inches

Bushing Thread Length:

Any acceptable

Cap Diameter:

Between 1.230 inches and 1.270 inches

Bushing Hole Diameter:

Between 1.126 inches and 1.131 inches

Flatted Side Bushing Hole Length:

Between 1.067 inches and 1.072 inches

Screw Thread Diameter:

0.190 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

33.0

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 threaded stud and 1 screw

Specification Data:

81349-mil-f-19207/24 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0