## NSN 5920-00-932-6979

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-932-6979 **Body Style:** Tangent terminal type **Terminal Material:** Brass **Terminal Surface Treatment:** Nickel **Overall Length:** Between 1.719 inches and 1.781 inches Center To Center Distance Between Mounting Facilities Parallel To Length: Between 0.969 inches and 1.031 inches **Overall Width:** Between 1.281 inches and 1.343 inches **Mounting Slot Width:** Between 0.259 inches and 0.260 inches **Overall Diameter:** Between 0.781 inches and 0.843 inches **Case Material:** Fiber or paper **Continuous Current Rating In Amps:** 125.000 **Terminal Thickness:** 0.047 inches **Maximum Voltage Rating In Volts:** 32.0 ac and 32.0 dc **Circuit Over-current Interruption Type:** 

Normal instantaneous

**Interruption Indicator Method:** 

Opaque body

**Features Provided:** 

Nonrenewable fusible element

**Short-circuit/interrupt Current Rating In Amps:** 

10000.0

**Test Data Document:** 

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:** 

81349-mil-f-15160/40 government specification

Shelf Life:

N/a

**Unit Of Measure:** 

**Demilitarization:** 

No

## **NSN 5920-00-932-6979**Cartridge Fuse - Page 2 of 2



Fiig:

A01700