

View Online at <https://aerobasegroup.com/nsn/5920-00-935-2275>

**Body Style:**

Bushing mounted type

**Overall Length:**

2.844 inches

**Bushing Diameter:**

0.625 inches

**Overall Width:**

0.812 inches

**Body Diameter:**

0.812 inches

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting

**Contact Material:**

Brass

**Contact Surface Treatment:**

Tin plated

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.250 inches

**Accommodated Ferrule Diameter:**

0.250 inches

**Resistor Rating:**

220.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+90.0/+250.0

**Length From Front Protrusion To Mounting Surface:**

1.188 inches

**Bushing Thread Length:**

0.438 inches

**Cap Diameter:**

0.500 inches

**Bushing Hole Diameter:**

0.630 inches

**Flatted Side Bushing Hole Length:**

0.590 inches

**Current Carrying Rating In Amps:**

20.0

**Criticality Code Justification:**

Feat

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

250.0

**Special Features:**

Knob color clear; as differentiated by navord od41152

**Supplementary Features:**

24nov00 item reviewed under girder project. Fg non-concur cancellation action

**Terminal Type And Quantity:**

2 tab, solder lug

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fiig:**

A014a0