

View Online at <https://aerobasegroup.com/nsn/5920-00-935-2275>

Body Style:

Bushing mounted type

Overall Length:

2.844 inches

Bushing Diameter:

0.625 inches

Overall Width:

0.812 inches

Body Diameter:

0.812 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Contact Material:

Brass

Contact Surface Treatment:

Tin plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

220.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+250.0

Length From Front Protrusion To Mounting Surface:

1.188 inches

Bushing Thread Length:

0.438 inches

Cap Diameter:

0.500 inches

Bushing Hole Diameter:

0.630 inches

Flatted Side Bushing Hole Length:

0.590 inches

Current Carrying Rating In Amps:

20.0

Criticality Code Justification:

Feat

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Special Features:

Knob color clear; as differentiated by navord od41152

Supplementary Features:

24nov00 item reviewed under girder project. Fg non-concur cancellation action

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0