## NSN 5920-00-936-3946



Cartridge Fuse - Page 1 of 2 View Online at https://aerobasegroup.com/nsn/5920-00-936-3946 **Body Style:** Plug-in type **Terminal Material:** Brass **Terminal Surface Treatment:** Nickel **Overall Length:** Between 0.498 inches and 0.538 inches **Terminal Length:** Between 0.160 inches and 0.180 inches **Body Length:** Between 0.338 inches and 0.358 inches **Overall Diameter:** Between 0.240 inches and 0.260 inches **Continuous Current Rating In Amps:** 0.500 **Terminal Diameter:** Between 0.024 inches and 0.026 inches Center To Center Distance Between Mounting Facilities Parallel To Diameter: Between 0.100 inches and 0.108 inches **Maximum Voltage Rating In Volts:** 125.0 ac and 125.0 dc **Circuit Over-current Interruption Type:** Normal instantaneous **Interruption Indicator Method:** Visible element **Features Provided:** Nonrenewable fusible element **Short-circuit/interrupt Current Rating In Amps:** 10000.0 **Test Data Document:** 81349-mil-prf-23419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81349-mil-prf-23419/2j government specification

format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.)

Specification Data:
81349-mil-prf-23419/2j government specification

Shelf Life:
N/a

Unit Of Measure:
-
Demilitarization:
No

Fiig:
A01700

## NSN 5920-00-936-3946

Cartridge Fuse - Page 2 of 2



Mil-std (military Standard):

Mil-prf-23419 spec.