## **NSN 5920-00-938-7660**Cartridge Fuse - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5920-00-938-7660  |
|--|
| Body Style:  |
| Plug-in type   |
| Terminal Material:   |
| Copper   |
| Terminal Surface Treatment:  |
| Nickel   |
| Overall Length:  |
| Between 0.498 inches and 0.538 inches  |
| Terminal Length:   |
| Between 0.160 inches and 0.180 inches  |
| Body Length:   |
| Between 0.338 inches and 0.358 inches  |
| Overall Diameter:  |
| Between 0.240 inches and 0.260 inches  |
| Case Material:   |
| Plastic  |
| Continuous Current Rating In Amps:   |
| 2.000  |
| Terminal Diameter:   |
| Between 0.024 inches and 0.026 inches  |
| Center To Center Distance Between Mounting Facilities Parallel To Diameter:  |
| Between 0.100 inches and 0.108 inches  |
| Maximum Voltage Rating In Volts:   |
| 125.0 ac and 125.0 dc  |
| Circuit Over-current Interruption Type:  |
| Normal instantaneous   |
| Interruption Indicator Method:   |
| Visible element  |
| Features Provided:   |
| Nonrenewable fusible element   |
| Short-circuit/interrupt Current Rating In Amps:  |
| 10000.0  |
| Precious Material And Location:  |
| Contact surfaces silver  |
| Precious Material:   |
| Silver   |
| Test Data Document:  |
| 81349-mil-f-23419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-f-23419/2 government specification   |

N/a

Shelf Life:

## **NSN 5920-00-938-7660**Cartridge Fuse - Page 2 of 2



|   |    | • • |             |          |  |
|---|----|-----|-------------|----------|--|
| ш | ın | 10  | <i>(</i> )+ | Measure: |  |
|   |    |     |             |          |  |

Demilitarization:

No

Fiig:

A01700