NSN 5920-00-938-7660Cartridge Fuse - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5920-00-938-7660 |
|--|
| Body Style: |
| Plug-in type |
| Terminal Material: |
| Copper |
| Terminal Surface Treatment: |
| Nickel |
| Overall Length: |
| Between 0.498 inches and 0.538 inches |
| Terminal Length: |
| Between 0.160 inches and 0.180 inches |
| Body Length: |
| Between 0.338 inches and 0.358 inches |
| Overall Diameter: |
| Between 0.240 inches and 0.260 inches |
| Case Material: |
| Plastic |
| Continuous Current Rating In Amps: |
| 2.000 |
| Terminal Diameter: |
| Between 0.024 inches and 0.026 inches |
| Center To Center Distance Between Mounting Facilities Parallel To Diameter: |
| Between 0.100 inches and 0.108 inches |
| Maximum Voltage Rating In Volts: |
| 125.0 ac and 125.0 dc |
| Circuit Over-current Interruption Type: |
| Normal instantaneous |
| Interruption Indicator Method: |
| Visible element |
| Features Provided: |
| Nonrenewable fusible element |
| Short-circuit/interrupt Current Rating In Amps: |
| 10000.0 |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material: |
| Silver |
| Test Data Document: |
| 81349-mil-f-23419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81349-mil-f-23419/2 government specification |

N/a

Shelf Life:

NSN 5920-00-938-7660Cartridge Fuse - Page 2 of 2



| | | • • | | | |
|---|----|-----|-------------|----------|--|
| ш | ın | 10 | <i>(</i>)+ | Measure: | |
| | | | | | |

Demilitarization:

No

Fiig:

A01700