

View Online at <https://aerobasegroup.com/nsn/5920-00-948-5765>

Body Material:

Plastic, polyester, mil-m-14, type mai-60

Body Style:

Panel mounted type

Overall Length:

Between 8.990 inches and 9.010 inches

Mounting Hole Diameter:

Between 0.279 inches and 0.283 inches

Mounting Hole Quantity:

3

Overall Diameter:

Between 2.980 inches and 3.020 inches

Panel Thickness:

0.250 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting w/3 holes

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Neon lamp

Shortest Center To Center Distance Between Mounting Holes Along Length:

Between 0.964 inches and 0.974 inches

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.000 inches

Accommodated Fuse Width:

Between 0.715 inches and 0.785 inches

Accommodated Fuse Thickness:

Between 0.122 inches and 0.128 inches

Resistor Rating:

160.0 kilohms and 160.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+500.0 and +90.0/+500.0

Length From Front Protrusion To Mounting Surface:

Between 1.870 inches and 1.880 inches

Cap Diameter:

Between 2.480 inches and 2.520 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

Between 1.928 inches and 1.948 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

Between 2.350 inches and 2.400 inches

Center To Center Distance Between Inside Mounting Holes Along Length:

Between 0.964 inches and 0.974 inches

Bushing Hole Diameter:

Between 2.182 inches and 2.192 inches

Center To Center Distance Between Bushing Hole And Mounting Hole:

Between 1.370 inches and 1.380 inches

Screw Thread Diameter:

0.312 inches

Screw Thread Qty Per Inch (tpi):

18.0

Current Carrying Rating In Amps:

1000.0

Fuse Terminal Type Accommodated:

Knife blade

Voltage In Volts:

500.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 threaded stud

Specification Data:

81349-mil-f-19207/6 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0