

View Online at <https://aerobasegroup.com/nsn/5920-00-948-5765>

**Body Material:**

Plastic, polyester, mil-m-14, type mai-60

**Body Style:**

Panel mounted type

**Overall Length:**

Between 8.990 inches and 9.010 inches

**Mounting Hole Diameter:**

Between 0.279 inches and 0.283 inches

**Mounting Hole Quantity:**

3

**Overall Diameter:**

Between 2.980 inches and 3.020 inches

**Panel Thickness:**

0.250 inches

**Environmental Protection:**

Dripproof

**Mounting Hole Style:**

Bushing mounting w/3 holes

**Contact Material:**

Any acceptable

**Contact Surface Treatment:**

Silver plated, qq-s-365

**Interruption Indicator Method:**

Neon lamp

**Shortest Center To Center Distance Between Mounting Holes Along Length:**

Between 0.964 inches and 0.974 inches

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.000 inches

**Accommodated Fuse Width:**

Between 0.715 inches and 0.785 inches

**Accommodated Fuse Thickness:**

Between 0.122 inches and 0.128 inches

**Resistor Rating:**

160.0 kilohms and 160.0 kilohms

**Indicating Lamp Voltage Range In Volts:**

+90.0/+500.0 and +90.0/+500.0

**Length From Front Protrusion To Mounting Surface:**

Between 1.870 inches and 1.880 inches

**Cap Diameter:**

Between 2.480 inches and 2.520 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

Between 1.928 inches and 1.948 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

Between 2.350 inches and 2.400 inches

**Center To Center Distance Between Inside Mounting Holes Along Length:**

Between 0.964 inches and 0.974 inches

**Bushing Hole Diameter:**

Between 2.182 inches and 2.192 inches

**Center To Center Distance Between Bushing Hole And Mounting Hole:**

Between 1.370 inches and 1.380 inches

**Screw Thread Diameter:**

0.312 inches

**Screw Thread Qty Per Inch (tpi):**

18.0

**Current Carrying Rating In Amps:**

1000.0

**Fuse Terminal Type Accommodated:**

Knife blade

**Voltage In Volts:**

500.0

**Precious Material And Location:**

Contact surfaces silver

**Precious Material:**

Silver

**Test Data Document:**

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Terminal Type And Quantity:**

2 threaded stud

**Specification Data:**

81349-mil-f-19207/6 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**

A014a0