NSN 5920-00-954-3079

Extractor Post Fuseholder - Page 1 of 2



3.	
View Online at https://aerobasegroup.com/nsn/5920-00-954-3079	
Body Material:	
Plastic	
Body Style:	
Panel mounted type	
Overall Length:	
Between 2.150 inches and 2.230 inches	
Overall Height:	
Between 2.260 inches and 2.300 inches	
Overall Width:	
Between 2.040 inches and 2.080 inches	
Mounting Hole Diameter:	
Between 0.147 inches and 0.157 inches	
Mounting Hole Quantity:	
1 and 3	
Panel Thickness:	
0.187 inches	
Environmental Protection:	
Watertight	
Mounting Hole Style:	
Panel mounting w/2 or 3 holes	
Contact Material:	
Any acceptable	
Contact Surface Treatment:	
Silver plated, qq-s-365	
Interruption Indicator Method:	
Neon lamp	
Fuse Accommodation Quantity:	
2	
Accommodated Fuse Length:	
1.500 inches	
Accommodated Ferrule Diameter:	

0.406 inches

Resistor Rating:

330.0 kilohms and 330.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+500.0 and +90.0/+500.0

Length From Front Protrusion To Mounting Surface:

Between 1.170 inches and 1.210 inches

Cap Diameter:

Between 0.600 inches and 0.640 inches

Mounting Hole Height:

Between 1.820 inches and 1.860 inches

NSN 5920-00-954-3079Extractor Post Fuseholder - Page 2 of 2



Mounting Hole Width:
Between 1.540 inches and 1.580 inches
Center To Center Distance Between Outside Mounting Holes Along Length:
Between 1.950 inches and 1.960 inches
Center To Center Distance Between Outside Mounting Holes Along Width:
Between 0.990 inches and 1.000 inches
Screw Thread Diameter:
0.164 inches
Screw Thready Qty Per Inch (tpi):
32.0
Current Carrying Rating In Amps:
30.0
Fuse Terminal Type Accommodated:
Ferrule
Voltage In Volts:
500.0
Precious Material And Location:
Contact surfaces silver
Precious Material:
Silver
Test Data Document:
81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Terminal Type And Quantity:
4 threaded stud
Specification Data:
81349-mil-f-19207/23 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A014a0