NSN 5920-00-954-3079

Extractor Post Fuseholder - Page 1 of 2



| 3. | |
|---|--|
| View Online at https://aerobasegroup.com/nsn/5920-00-954-3079 | |
| Body Material: | |
| Plastic | |
| Body Style: | |
| Panel mounted type | |
| Overall Length: | |
| Between 2.150 inches and 2.230 inches | |
| Overall Height: | |
| Between 2.260 inches and 2.300 inches | |
| Overall Width: | |
| Between 2.040 inches and 2.080 inches | |
| Mounting Hole Diameter: | |
| Between 0.147 inches and 0.157 inches | |
| Mounting Hole Quantity: | |
| 1 and 3 | |
| Panel Thickness: | |
| 0.187 inches | |
| Environmental Protection: | |
| Watertight | |
| Mounting Hole Style: | |
| Panel mounting w/2 or 3 holes | |
| Contact Material: | |
| Any acceptable | |
| Contact Surface Treatment: | |
| Silver plated, qq-s-365 | |
| Interruption Indicator Method: | |
| Neon lamp | |
| Fuse Accommodation Quantity: | |
| 2 | |
| Accommodated Fuse Length: | |
| 1.500 inches | |
| Accommodated Ferrule Diameter: | |
| | |

0.406 inches

Resistor Rating:

330.0 kilohms and 330.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+500.0 and +90.0/+500.0

Length From Front Protrusion To Mounting Surface:

Between 1.170 inches and 1.210 inches

Cap Diameter:

Between 0.600 inches and 0.640 inches

Mounting Hole Height:

Between 1.820 inches and 1.860 inches

NSN 5920-00-954-3079Extractor Post Fuseholder - Page 2 of 2



| Mounting Hole Width: |
|--|
| Between 1.540 inches and 1.580 inches |
| Center To Center Distance Between Outside Mounting Holes Along Length: |
| Between 1.950 inches and 1.960 inches |
| Center To Center Distance Between Outside Mounting Holes Along Width: |
| Between 0.990 inches and 1.000 inches |
| Screw Thread Diameter: |
| 0.164 inches |
| Screw Thready Qty Per Inch (tpi): |
| 32.0 |
| Current Carrying Rating In Amps: |
| 30.0 |
| Fuse Terminal Type Accommodated: |
| Ferrule |
| Voltage In Volts: |
| 500.0 |
| Precious Material And Location: |
| Contact surfaces silver |
| Precious Material: |
| Silver |
| Test Data Document: |
| 81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Terminal Type And Quantity: |
| 4 threaded stud |
| Specification Data: |
| 81349-mil-f-19207/23 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A014a0 |