

View Online at <https://aerobasegroup.com/nsn/5920-00-964-4384>

Body Material:

Plastic, mil-p-14, type mai-60

Body Style:

Bushing mounted type

Overall Length:

Between 2.350 inches and 2.390 inches

Bushing Diameter:

0.625 inches

Mounting Hole Quantity:

1

Overall Diameter:

1.240 inches

Panel Thickness:

0.125 inches

Environmental Protection:

Watertight and body sealed

Mounting Hole Style:

Bushing mounting

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

Between 0.540 inches and 0.580 inches

Bushing Thread Length:

0.175 inches

Cap Diameter:

Between 0.600 inches and 0.640 inches

Bushing Hole Diameter:

Between 0.625 inches and 0.635 inches

Flatted Side Bushing Hole Length:

Between 0.590 inches and 0.595 inches

Screw Thread Diameter:

0.138 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

1 threaded stud and 1 screw

Specification Data:

81349-mil-f-19207/17 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0