

View Online at <https://aerobasegroup.com/nsn/5920-00-981-5803>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type mdg and plastic, diallyl phthalate, mil-m-14, type sdg and plastic, melamine, mil-m-14, type mme and plastic, silicone, mil-m-14, type msg

Body Style:

Clip connected type

Terminal Material:

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

Between 7.360 inches and 7.400 inches

Overall Height:

Between 0.680 inches and 0.720 inches

Overall Width:

Between 1.600 inches and 1.640 inches

Mounting Hole Diameter:

0.138 inches

Mounting Hole Quantity:

1

Base Thickness:

Between 0.230 inches and 0.270 inches

Mounting Hole Style:

One hole mounting

Contact Material:

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

Contact Surface Treatment:

Any acceptable

Fuse Accommodation Quantity:

12

Accommodated Fuse Length:

Between 1.219 inches and 1.281 inches

Accommodated Ferrule Diameter:

Between 0.246 inches and 0.254 inches

Current Carrying Rating In Amps:

20.0

Internal Circuit Configuration And Pole Quantity:

12 pole, mainline, fused

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Test Data Document:

81349-mil-f-21346 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical" "average" "" etc.)

Terminal Type And Quantity:

24 tab, solder lug

Specification Data:

81349-aa55518/02-018 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0