NSN 5920-00-982-8023

Block Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-00-982-8023

Body Material:

Plastic, diallyl phthalate, mil-m-14, type mdg and plastic, diallyl phthalate, mil-m-14, type sdg and plastic, melamine, mil-m-14, type mme and plastic, silicone, mil-m-14, type msg

Body Style:

Clip connected type

Terminal Material:

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

Between 2.360 inches and 2.400 inches

Overall Height:

Between 0.680 inches and 0.720 inches

Overall Width:

Between 1.670 inches and 1.710 inches

Mounting Hole Diameter:

0.138 inches

Mounting Hole Quantity:

...

Base Thickness:

Between 0.230 inches and 0.270 inches

Mounting Hole Style:

One hole mounting

Contact Material:

Copper-beryllium, qq-c-530 or copper-beryllium, qq-c-533

Contact Surface Treatment:

Copper and tin plated and zinc plated

Fuse Accommodation Quantity:

2

Accommodated Fuse Length:

Between 1.219 inches and 1.281 inches

Accommodated Ferrule Diameter:

Between 0.246 inches and 0.254 inches

Current Carrying Rating In Amps:

30.0

Internal Circuit Configuration And Pole Quantity:

2 pole, mainline, fused

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Test Data Document:

81349-mil-f-21346 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain

NSN 5920-00-982-8023

Block Fuseholder - Page 2 of 2



Terminal Type And Quantity:
4 screw
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:

No **Fiig:**

A014a0