

View Online at <https://aerobasegroup.com/nsn/5920-00-990-9727>

Body Material:

Plastic, diallyl phthalate, mil-m-14, type sdg

Body Style:

Bushing mounted type

Terminal Surface Treatment:

Solder dip

Overall Length:

Between 2.278 inches and 2.840 inches

Bushing Diameter:

0.625 inches

Overall Width:

0.688 inches

Body Diameter:

Between 0.780 inches and 0.840 inches

Mounting Hole Diameter:

0.625 inches

Mounting Hole Quantity:

1

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Contact Material:

Brass, qq-b-613

Contact Surface Treatment:

Tin plated

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.250 inches

Accommodated Ferrule Diameter:

0.250 inches

Resistor Rating:

220.0 kilohms

Indicating Lamp Voltage Range In Volts:

+90.0/+250.0

Length From Front Protrusion To Mounting Surface:

Between 1.150 inches and 1.210 inches

Bushing Thread Length:

Between 0.400 inches and 0.460 inches

Cap Diameter:

0.812 inches

Bushing Hole Diameter:

Between 0.625 inches and 0.635 inches

Flatted Side Bushing Hole Length:

Between 0.550 inches and 0.582 inches

Current Carrying Rating In Amps:

15.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

300.0

Terminal Type And Quantity:

2 tab, solder lug

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig:

A014a0