

View Online at <https://aerobasegroup.com/nsn/5920-00-995-0431>

Body Material:

Plastic, diallyl phthalate, mil-m-19833, type gdi-30f

Body Style:

Panel mounted type

Terminal Surface Treatment:

Solder dip and tin plated

Overall Length:

Between 1.132 inches and 1.179 inches

Bushing Diameter:

0.625 inches

Mounting Hole Quantity:

1

Overall Diameter:

Between 0.760 inches and 0.800 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Contact Material:

Any acceptable

Contact Surface Treatment:

Silver plated, qq-s-365

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

Between 0.498 inches and 0.538 inches

Resistor Rating:

2.0 kilohms

Indicating Lamp Voltage Range In Volts:

+81.0/+90.0

Length From Front Protrusion To Mounting Surface:

Between 0.530 inches and 0.570 inches

Bushing Thread Length:

Between 0.120 inches and 0.130 inches

Bushing Hole Diameter:

Between 0.625 inches and 0.635 inches

Flatted Side Bushing Hole Length:

Between 0.570 inches and 0.575 inches

Current Carrying Rating In Amps:

5.0

Fuse Terminal Type Accommodated:

Pin

Voltage In Volts:

125.0

Precious Material And Location:

Contact surfaces silver

Precious Material:

Silver

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-f-19207/28 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0