NSN 5920-01-028-9302

Body Material:

Extractor Post Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-028-9302

| Plastic, diallyl phthalate, mil-m-14, type sdg |
|---|
| Body Style: |
| Bushing mounted type |
| Terminal Material: |
| Brass |
| Terminal Surface Treatment: |
| Silver plated, qq-s-365 |
| Overall Length: |
| 2.840 inches |
| Bushing Diameter: |
| 0.625 inches |
| Mounting Hole Quantity: |
| 1 |
| Overall Diameter: |
| Between 0.800 inches and 0.840 inches |
| Environmental Protection: |
| Dripproof |
| Mounting Hole Style: |
| Bushing mounting |
| Lens Color: |
| Clear |
| Contact Material: |
| Brass |
| Contact Surface Treatment: |
| Silver plated, qq-s-365 |
| Interruption Indicator Method: |
| Neon lamp |
| Fuse Accommodation Quantity: |
| 1 |
| Accommodated Fuse Length: |
| 1.250 inches |
| Accommodated Ferrule Diameter: |
| 0.250 inches |
| Length From Front Protrusion To Mounting Surface: |
| Between 1.170 inches and 1.210 inches |
| Bushing Thread Length: |
| Between 0.420 inches and 0.460 inches |
| Bushing Hole Diameter: |
| Between 0.625 inches and 0.635 inches |
| Flatted Side Rushing Hole Length: |

Between 0.570 inches and 0.575 inches

NSN 5920-01-028-9302

Extractor Post Fuseholder - Page 2 of 2



| Current Carrying Rating In Amps: |
|----------------------------------|
| 20.0 |
| Fuse Terminal Type Accommodated: |
| Ferrule |
| Voltage In Volts: |
| 250.0 |
| Special Features: |
| Less resistor |
| Precious Material And Location: |
| Terminal surface silver |
| Precious Material: |
| Silver |
| Terminal Type And Quantity: |
| 2 tab, solder lug |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |
| No |
| Fiig: |
| A014a0 |