## **NSN 5920-01-106-7549**Cartridge Fuse - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5920-01-106-7549  |
|--|
| Body Style:  |
| Knife blade type   |
| Terminal Material:   |
| Brass or copper or bronze or copper alloy  |
| Terminal Surface Treatment:  |
| Silver plated  |
| Overall Length:  |
| Between 8.532 inches and 8.718 inches  |
| Terminal Length:   |
| 1.880 inches   |
| Overall Diameter:  |
| 2.410 inches   |
| Case Material:   |
| Plastic, melamine, glass filled  |
| Continuous Current Rating In Amps:   |
| 400.000  |
| Terminal Width:  |
| Between 1.590 inches and 1.660 inches  |
| Terminal Thickness:  |
| Between 0.247 inches and 0.253 inches  |
| Maximum Voltage Rating In Volts:   |
| 500.0 ac and 500.0 dc  |
| Circuit Over-current Interruption Type:  |
| Normal instantaneous   |
| Interruption Indicator Method:   |
| Opaque body  |
| Features Provided:   |
| Nonrenewable fusible element   |
| Short-circuit/interrupt Current Rating In Amps:  |
| 150000.0 and 200000.0  |
| Precious Material And Location:  |
| Terminal surface silver  |
| Precious Material:   |
| Silver   |
| Test Data Document:  |
| 81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification |
| format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain          |
| environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).                            |
| Specification Data:  |
| 81349-mil-f-15160/65 government specification  |
| Shelf Life:  |
| N/a  |

**Unit Of Measure:** 

## NSN 5920-01-106-7549

Cartridge Fuse - Page 2 of 2



Demilitarization:

No

Fiig:

A01700