

View Online at <https://aerobasegroup.com/nsn/5920-01-127-3541>

**Body Style:**

Tube type

**Terminal Material:**

Brass or copper or copper alloy

**Terminal Surface Treatment:**

Nickel

**Overall Length:**

1.250 inches

**Overall Diameter:**

0.250 inches

**Case Material:**

Plastic or ceramic

**Continuous Current Rating In Amps:**

0.125

**Maximum Voltage Rating In Volts:**

250.0 ac and 250.0 dc

**Circuit Over-current Interruption Type:**

Normal instantaneous

**Interruption Indicator Method:**

Opaque body

**End Application:**

Spruance class dd (963); blue ridge class lcc-19; forrestal class cv; general purpose electronic test equipment gpete; aircraft, hawkkey e-2c; fire control system, mk 92 (fcs); kidd class ddg; ticonderoga class cg (47); usns henry j. Kaiser class tao; mercy and comfort hospital ships class tah

**Features Provided:**

Nonrenewable fusible element

**Criticality Code Justification:**

Feat

**Short-circuit/interrupt Current Rating In Amps:**

35.0

**Special Features:**

Weapon system essential

**Test Data Document:**

81349-mil-f-23419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

**Specification Data:**

81349-mil-f-23419/9 government specification

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

No

**Fig:**