

View Online at <https://aerobasegroup.com/nsn/5920-01-127-3541>

Body Style:

Tube type

Terminal Material:

Brass or copper or copper alloy

Terminal Surface Treatment:

Nickel

Overall Length:

1.250 inches

Overall Diameter:

0.250 inches

Case Material:

Plastic or ceramic

Continuous Current Rating In Amps:

0.125

Maximum Voltage Rating In Volts:

250.0 ac and 250.0 dc

Circuit Over-current Interruption Type:

Normal instantaneous

Interruption Indicator Method:

Opaque body

End Application:

Spruance class dd (963); blue ridge class lcc-19; forrestal class cv; general purpose electronic test equipment gpete; aircraft, hawkkey e-2c; fire control system, mk 92 (fcs); kidd class ddg; ticonderoga class cg (47); usns henry j. Kaiser class tao; mercy and comfort hospital ships class tah

Features Provided:

Nonrenewable fusible element

Criticality Code Justification:

Feat

Short-circuit/interrupt Current Rating In Amps:

35.0

Special Features:

Weapon system essential

Test Data Document:

81349-mil-f-23419 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-23419/9 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fig: