NSN 5920-01-140-9624

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-01-140-9624

Body Style: Tube type Terminal Material: Copper alloy Terminal Surface Treatment: Nickel plated Overall Length: 1.500 inches Overall Diameter: 0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Terminal Material: Copper alloy Terminal Surface Treatment: Nickel plated Overall Length: 1.500 inches Overall Diameter: 0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Copper alloy Terminal Surface Treatment: Nickel plated Overall Length: 1.500 inches Overall Diameter: 0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Terminal Surface Treatment: Nickel plated Overall Length: 1.500 inches Overall Diameter: 0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Nickel plated Overall Length: 1.500 inches Overall Diameter: 0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Overall Length: 1.500 inches Overall Diameter: 0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
1.500 inches Overall Diameter: 0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Overall Diameter: 0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
0.406 inches Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Continuous Current Rating In Amps: 15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
15.000 Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Maximum Voltage Rating In Volts: 250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
250.0 ac and 250.0 dc Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Circuit Over-current Interruption Type: Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Normal instantaneous Interruption Indicator Method: Opaque body Features Provided:
Interruption Indicator Method: Opaque body Features Provided:
Opaque body Features Provided:
Features Provided:
New your share the first black and the
Nonrenewable fusible element
Short-circuit/interrupt Current Rating In Amps:
200000.0
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A01700