NSN 5920-01-161-8120

Cartridge Fuse - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-01-161-8120

Body Style:
Tube type
Terminal Material:
Brass or copper or copper alloy
Terminal Surface Treatment:
Nickel
Overall Length:
5.000 inches
Overall Diameter:
0.812 inches
Case Material:
Fiber or ceramic or plastic, melamine, glass filled
Continuous Current Rating In Amps:
20.000
Maximum Voltage Rating In Volts:
600.0 ac and 600.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
10.0 500 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
200000.0
Special Features:
Groove in one ferrule prevents use of class h fuses equipment designed for class r type
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/62 government specification
Shelf Life:
N/a
Unit Of Measure:
Demilitarization:
No
Fiig:
A01700