NSN 5920-01-189-5288

Block Fuseholder - Page 1 of 1



View Online at https://aerobasegroup.com/nsn/5920-01-189-5288

Contact Material: Copper Contact Surface Treatment: Nickel plated Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0	Body Material:
16.062 inches Overall Width: 4.750 inches Contact Material: Copper Contact Surface Treatment: Nickel plated Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Plastic
Overall Width: 4.750 inches Contact Material: Copper Contact Surface Treatment: Nickel plated Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Overall Length:
4.750 inches Contact Material: Copper Contact Surface Treatment: Nickel plated Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	16.062 inches
Contact Material: Copper Contact Surface Treatment: Nickel plated Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Overall Width:
Copper Contact Surface Treatment: Nickel plated Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure: 	4.750 inches
Contact Surface Treatment: Nickel plated Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Contact Material:
Nickel plated Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Copper
Fuse Accommodation Quantity: 5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Contact Surface Treatment:
5 Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Nickel plated
Accommodated Fuse Length: 1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Fuse Accommodation Quantity:
1.250 inches Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	5
Accommodated Ferrule Diameter: Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Accommodated Fuse Length:
Between 0.250 inches and 0.380 inches Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	1.250 inches
Current Carrying Rating In Amps: 30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Accommodated Ferrule Diameter:
30.0 Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Between 0.250 inches and 0.380 inches
Internal Circuit Configuration And Pole Quantity: 5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Current Carrying Rating In Amps:
5 pole, mainline, fused Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	30.0
Fuse Terminal Type Accommodated: Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Internal Circuit Configuration And Pole Quantity:
Ferrule Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	5 pole, mainline, fused
Voltage In Volts: 250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Fuse Terminal Type Accommodated:
250.0 Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure: 	Ferrule
Terminal Type And Quantity: 10 tab, solder lug Shelf Life: N/a Unit Of Measure:	Voltage In Volts:
10 tab, solder lug Shelf Life: N/a Unit Of Measure:	250.0
Shelf Life: N/a Unit Of Measure:	Terminal Type And Quantity:
N/a Unit Of Measure: 	10 tab, solder lug
Unit Of Measure:	Shelf Life:
	N/a
 Demilitarization:	Unit Of Measure:
Demilitarization:	
	Demilitarization:
No	No
Fiig:	Fiig:
A014a0	A014a0