# NSN 5920-01-195-7252

Block Fuseholder - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-195-7252

## **Body Material:**

Plastic, phenolic, moulded

**Body Style:** 

Side barrier type

## **Terminal Material:**

Copper

## **Terminal Surface Treatment:**

Tin plated

#### **Overall Length:**

6.750 inches

#### **Overall Height:**

2.125 inches

#### **Overall Width:**

3.500 inches

#### Mounting Hole Diameter:

#### 0.281 inches

Mounting Hole Quantity:

4

Base Thickness:

0.750 inches

#### Mounting Hole Style:

4 hole mounting-irregular spaced

#### **Contact Material:**

Copper

#### **Contact Surface Treatment:**

Nickel plated

#### Shortest Center To Center Distance Between Mounting Holes Along Length:

0.625 inches

**Fuse Accommodation Quantity:** 

2

# Accommodated Fuse Length:

5.000 inches

# Accommodated Ferrule Diameter:

0.812 inches

# Center To Center Distance Between Outside Mounting Holes Along Length:

2.187 inches

# Center To Center Distance Between Outside Mounting Holes Along Width:

3.125 inches

Center To Center Distance Between Inside Mounting Holes Along Length:

0.625 inches

# **Current Carrying Rating In Amps:**

30.0

NSN 5920-01-195-7252

Block Fuseholder - Page 2 of 2



## Internal Circuit Configuration And Pole Quantity:

2 pole, mainline, fused

## Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

600.0

## Terminal Type And Quantity:

4 compression

Shelf Life:

N/a

Unit Of Measure:

---

Demilitarization:

No

Fiig:

A014a0