

View Online at <https://aerobasegroup.com/nsn/5920-01-200-6274>

Body Material:

Plastic, phenolic, moulded

Body Style:

Bushing mounted type

Terminal Material:

Copper

Terminal Surface Treatment:

Nickel plated

Overall Length:

2.219 inches

Bushing Diameter:

0.500 inches

Mounting Hole Quantity:

1

Overall Diameter:

0.719 inches

Environmental Protection:

Dripproof

Mounting Hole Style:

Bushing mounting

Lens Color:

Clear

Contact Material:

Copper

Contact Surface Treatment:

Nickel plated

Interruption Indicator Method:

Test hole

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.000 inches

Accommodated Ferrule Diameter:

0.250 inches

Length From Front Protrusion To Mounting Surface:

0.532 inches

Bushing Thread Length:

0.843 inches

Cap Diameter:

0.719 inches

Bushing Hole Diameter:

Between 0.500 inches and 0.510 inches

Flatted Side Bushing Hole Length:

Between 0.468 inches and 0.478 inches

Current Carrying Rating In Amps:

5.0

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

250.0

Test Data Document:

81349-mil-f-19207 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Terminal Type And Quantity:

2 tab, solder lug

Specification Data:

81349-mil-f-19207/20 government specification

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

No

Fiig:

A014a0