NSN 5920-01-213-1513

Cartridge Fuse - Page 1 of 2



| View Online at https://aerobasegroup.com/nsn/5920-01-213-1513 |
|---|
| Body Style: |
| Axial terminal type |
| Terminal Material: |
| Copper or copper alloy |
| Terminal Surface Treatment: |
| Nickel |
| Overall Length: |
| 9.625 inches |
| Mounting Slot Width: |
| 0.281 inches |
| Body Length: |
| 6.450 inches |
| Overall Diameter: |
| 2.120 inches |
| Case Material: |
| Fiber or ceramic or plastic, melamine, glass filled |
| Continuous Current Rating In Amps: |
| 200.000 |
| Terminal Width: |
| 1.125 inches |
| Terminal Thickness: |
| 0.188 inches |
| Maximum Voltage Rating In Volts: |
| 600.0 ac and 600.0 dc |
| Circuit Over-current Interruption Type: |
| Normal instantaneous |
| Interruption Indicator Method: |
| Opaque body |
| Features Provided: |
| Nonrenewable fusible element |
| Short-circuit/interrupt Current Rating In Amps: |
| 200000.0 |
| Test Data Document: |
| 81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; |
| excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental |
| and performance requirements and test conditions that are shown as "typical", "average", "", etc.). |
| Specification Data: |
| 81348-w-f-1814/65 government specification |
| Shelf Life: |
| N/a |
| Unit Of Measure: |
| |
| Demilitarization: |

No

NSN 5920-01-213-1513Cartridge Fuse - Page 2 of 2



Fiig:

A01700