NSN 5920-01-219-6297

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-219-6297

view Offiline at https://defobasegroup.com/hsh/oszo-of-z15-ozs/
Body Style:
Tube type
Terminal Material:
Brass or copper or phosphor bronze
Overall Length:
Between 1.219 inches and 1.281 inches
Overall Diameter:
Between 0.246 inches and 0.254 inches
Case Material:
Glass
Continuous Current Rating In Amps:
1.500
Fragility Factor:
Delicate
Maximum Voltage Rating In Volts:
125.0 ac and 125.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Visible element
End Application:
6515-00-137-6511electrosurgical app. Model sse2l
Features Provided:
Nonrenewable fusible element
Cubic Measure:
0.0002 cubic inches
Circuit Over-current Interruption Delay Time In Seconds:
12.0 200 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
10000.0
Test Data Document:
81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification
format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain
environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81349-mil-f-15160/2 government specification
Purchase Description Identification:
52385-a215017012
Shelf Life:
N/a
Unit Of Measure:
-

No

Demilitarization:

NSN 5920-01-219-6297Cartridge Fuse - Page 2 of 2



Fiig:

A01700