NSN 5920-01-219-6297

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-219-6297

Body Style:

Tube type

Terminal Material:

Brass or copper or phosphor bronze

Overall Length:

Between 1.219 inches and 1.281 inches

Overall Diameter:

Between 0.246 inches and 0.254 inches

Case Material:

Glass

Continuous Current Rating In Amps:

1.500

Fragility Factor:

Delicate

Maximum Voltage Rating In Volts:

125.0 ac and 125.0 dc

Circuit Over-current Interruption Type:

Time delay

Interruption Indicator Method:

Visible element

End Application:

6515-00-137-6511electrosurgical app. Model sse2l

Features Provided:

Nonrenewable fusible element

Cubic Measure:

0.0002 cubic inches

Circuit Over-current Interruption Delay Time In Seconds:

12.0 200 pct of current rating

Short-circuit/interrupt Current Rating In Amps:

10000.0

Test Data Document:

81349-mil-f-15160 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

Specification Data:

81349-mil-f-15160/2 government specification

Purchase Description Identification:

52385-a215017012

Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

NSN 5920-01-219-6297 Cartridge Fuse - Page 2 of 2

Fiig: A01700

