

View Online at <https://aerobasegroup.com/nsn/5920-01-220-1911>

**Body Style:**

Rear panel mounted type

**Overall Length:**

Between 4.000 inches and 4.250 inches

**Overall Height:**

1.375 inches

**Overall Width:**

1.375 inches

**Keyway Width:**

0.145 inches

**Environmental Protection:**

Salt spray proof

**Mounting Hole Style:**

Bushing mounting w/2 holes and keyway

**Lens Color:**

Clear

**Interruption Indicator Method:**

Neon lamp

**Fuse Accommodation Quantity:**

1

**Accommodated Fuse Length:**

1.500 inches

**Accommodated Ferrule Diameter:**

0.406 inches

**Resistor Rating:**

330.0 kilohms

**Length From Front Protrusion To Mounting Surface:**

Between 0.798 inches and 0.828 inches

**Center To Center Distance Between Outside Mounting Holes Along Length:**

1.062 inches

**Center To Center Distance Between Outside Mounting Holes Along Width:**

1.062 inches

**Bushing Hole Diameter:**

1.145 inches

**Center To Center Distance Between Keyway And Bushing Hole:**

0.531 inches

**Screw Thread Diameter:**

0.164 inches

**Screw Thready Qty Per Inch (tpi):**

32.0

**Current Carrying Rating In Amps:**

30.0

**Criticality Code Justification:**

Zzzw

**Fuse Terminal Type Accommodated:**

Ferrule

**Voltage In Volts:**

500.0

**Terminal Type And Quantity:**

2 threaded stud

**Departure From Cited Document:**

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

**Shelf Life:**

N/a

**Unit Of Measure:**

--

**Demilitarization:**

Yes - demil/mli

**Fig:**

A014a0