

View Online at <https://aerobasegroup.com/nsn/5920-01-220-1911>

Body Style:

Rear panel mounted type

Overall Length:

Between 4.000 inches and 4.250 inches

Overall Height:

1.375 inches

Overall Width:

1.375 inches

Keyway Width:

0.145 inches

Environmental Protection:

Salt spray proof

Mounting Hole Style:

Bushing mounting w/2 holes and keyway

Lens Color:

Clear

Interruption Indicator Method:

Neon lamp

Fuse Accommodation Quantity:

1

Accommodated Fuse Length:

1.500 inches

Accommodated Ferrule Diameter:

0.406 inches

Resistor Rating:

330.0 kilohms

Length From Front Protrusion To Mounting Surface:

Between 0.798 inches and 0.828 inches

Center To Center Distance Between Outside Mounting Holes Along Length:

1.062 inches

Center To Center Distance Between Outside Mounting Holes Along Width:

1.062 inches

Bushing Hole Diameter:

1.145 inches

Center To Center Distance Between Keyway And Bushing Hole:

0.531 inches

Screw Thread Diameter:

0.164 inches

Screw Thready Qty Per Inch (tpi):

32.0

Current Carrying Rating In Amps:

30.0

Criticality Code Justification:

Zzzw

Fuse Terminal Type Accommodated:

Ferrule

Voltage In Volts:

500.0

Terminal Type And Quantity:

2 threaded stud

Departure From Cited Document:

Material will be in accordance with ships parts control center activity hx quality control, manufacturing and testing specifications

Shelf Life:

N/a

Unit Of Measure:

--

Demilitarization:

Yes - demil/mli

Fig:

A014a0