## NSN 5920-01-224-6161

Cartridge Fuse - Page 1 of 2

**Body Style:** 

Axial terminal type



View Online at https://aerobasegroup.com/nsn/5920-01-224-6161

Terminal Material:
Copper or copper alloy
Overall Length:
Between 8.530 inches and 8.710 inches
Mounting Slot Width:
0.406 inches
Body Length:
4.719 inches
Overall Diameter:
2.410 inches
Case Material:
Fiber or ceramic or plastic, melamine, glass filled
Continuous Current Rating In Amps:
225.000
Terminal Width:
Between 1.590 inches and 1.660 inches
Terminal Thickness:
Between 0.247 inches and 0.253 inches
Maximum Voltage Rating In Volts:
250.0 ac and 250.0 dc
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
10.0 500 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
200000.0
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/60 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:
No

## NSN 5920-01-224-6161

Cartridge Fuse - Page 2 of 2



Fiig:

A01700