NSN 5920-01-224-6530

No **Fiig:** A01700



Cartridge Fuse - Page 1 of 1 View Online at https://aerobasegroup.com/nsn/5920-01-224-6530 **Body Style:** Rejection groove type **Terminal Material:** Brass or copper or copper alloy **Terminal Surface Treatment:** Nickel plated **Overall Length:** Between 4.970 inches and 5.030 inches **Overall Diameter:** Between 0.804 inches and 0.820 inches **Case Material:** Fiber or ceramic or plastic, melamine, glass filled **Continuous Current Rating In Amps:** 2.250 **Maximum Voltage Rating In Volts:** 600.0 ac and 600.0 dc **Circuit Over-current Interruption Type:** Time delay **Interruption Indicator Method:** Opaque body **Features Provided:** Nonrenewable fusible element Circuit Over-current Interruption Delay Time In Seconds: 10.0 500 pct of current rating **Short-circuit/interrupt Current Rating In Amps:** 200000.0 **Test Data Document:** 81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.). **Specification Data:** 81348-w-f-1814/62 government specification Shelf Life: N/a **Unit Of Measure: Demilitarization:**