# NSN 5920-01-249-1903

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-249-1903

## Body Style:

Axial terminal type

#### **Terminal Material:**

Copper or copper alloy

### **Overall Length:**

7.875 inches

#### Mounting Slot Width:

0.281 inches

#### Body Length:

Between 5.375 inches and 5.781 inches

#### **Overall Diameter:**

1.560 inches

#### Case Material:

Fiber or ceramic or plastic, melamine, glass filled

#### **Continuous Current Rating In Amps:**

100.000

#### Terminal Width:

0.750 inches

#### **Terminal Thickness:**

0.125 inches

#### Maximum Voltage Rating In Volts:

600.0 ac and 600.0 dc

#### **Circuit Over-current Interruption Type:**

Time delay

#### Interruption Indicator Method:

Opaque body

#### **Features Provided:**

Nonrenewable fusible element

# Circuit Over-current Interruption Delay Time In Seconds:

10.0 500 pct of current rating

# Short-circuit/interrupt Current Rating In Amps:

200000.0

# Test Data Document:

81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format; excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental and performance requirements and test conditions that are shown as "typical", "average", "", etc.).

#### **Specification Data:**

81348-w-f-1814/64 government specification

#### Shelf Life:

N/a

- Unit Of Measure:
- --
- Demilitarization:
- No

# **NSN 5920-01-249-1903** Cartridge Fuse - Page 2 of 2

Fiig: A01700

