## NSN 5920-01-252-0615

Cartridge Fuse - Page 1 of 2



View Online at https://aerobasegroup.com/nsn/5920-01-252-0615

Body Style:
Rejection groove type
Terminal Material:
Copper or copper alloy
Overall Length:
5.880 inches
Mounting Slot Width:
0.281 inches
Body Length:
Between 3.375 inches and 3.781 inches
Overall Diameter:
1.310 inches
Case Material:
Fiber
Continuous Current Rating In Amps:
100.000
Terminal Width:
0.750 inches
Terminal Thickness:
0.125 inches
Maximum Voltage Rating In Volts:
250.0 ac
Circuit Over-current Interruption Type:
Time delay
Interruption Indicator Method:
Opaque body
Features Provided:
Nonrenewable fusible element
Circuit Over-current Interruption Delay Time In Seconds:
10.0 200 pct of current rating
Short-circuit/interrupt Current Rating In Amps:
200000.0
Test Data Document:
81348-w-f-1814 specification (includes engineering type bulletins, brochures, etc., that reflect specification type data in specification format;
excludes commercial catalogs, industry directories, and similar trade publications, reflecting general type data on certain environmental
and performance requirements and test conditions that are shown as "typical", "average", "", etc.).
Specification Data:
81348-w-f-1814/58 government specification
Shelf Life:
N/a
Unit Of Measure:
<del></del>
Demilitarization:

No

## **NSN 5920-01-252-0615**Cartridge Fuse - Page 2 of 2



Fiig:

A01700